

SASSO 60 round adjustable

trimless

048-2622614F 048-2696117 002-90771



Project / Type


Notes

Count / Date



Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; UGR ≤ 19; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed

tilt max 30°

rotation 360°

matt silver

Mounting set traffic white

front IP40 , back IP20

1080 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_r: 90 , R₍₁₋₅₎: 89

MR 0.81

MDER 0.74

Optical

flood

beam angle 39°

UGR < 19

P_{stLM} ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

non DIM

12.6 W

PC2 220-240V

86 lm/W

Physical

trimless

diameter 73 mm

height 48 mm

0.22 kg

Cutout

diameter 73 mm

recessed depth 60 mm

¹ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

