

# SASSO 60 round adjustable

trimless

048-2622514S 048-2696117 002-90771



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed  
 tilt max 30°  
 rotation 360°  
 matt silver  
 Mounting set traffic white  
 front IP40 , back IP20  
 601 lm

## LED

3000 K  
 CRI ≥ 90  
 initial MacAdam ≤ 3 SDCM

## Optical

spot  
 beam angle 12°  
 UGR < 16 , ≥65° <1500 cd/m<sup>2</sup>  
 PstLM ≤ 1.0<sup>1</sup>  
 SVM ≤ 0.4<sup>1</sup>

## Electrical

non DIM  
 13.1 W  
 PC2 220-240V  
 46 lm/W

## Physical

trimless  
 diameter 73 mm  
 height 48 mm  
 0.22 kg


## Cutout

diameter 73 mm  
 recessed depth 60 mm


<sup>1</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m<sup>2</sup>; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

