

SASSO 60 round adjustable

trim 2 lamps

048-2622511M 048-2698317 002-90762



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Recessed _____
 tilt max 30° _____
 rotation 360° _____
 black , RAL9005 ¹ _____
 Mounting set traffic white _____
 front IP40 , back IP20 _____
 1760 lm _____

LED

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000 h _____
 initial MacAdam ≤ 2 SDCM _____
 R_g: 100 , R_r: 91 , R_(f1-5): 88 _____
 MR 0.59 _____
 MDER 0.53 _____

Optical

medium _____
 beam angle 21° _____
 UGR < 16 _____
 PstLM ≤ 1.0 ² _____
 SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____
 25.2 W _____
 total insets 21.4 W _____
 PC2 220-240V _____
 70 lm/W _____
 1 DALI Addr. _____

Physical

trim _____
 length 147 mm _____
 width 80 mm _____
 height 48 mm _____
 0.32 kg _____


Cutout

diameter 70 mm _____
 length 136 mm _____
 min. ceiling thickness 2 mm _____
 max. ceiling thickness 25 mm _____
 recessed depth 110 mm _____


¹ RAL code ² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 2 lamps; surface black; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 21° beam; UGR ≤ 16; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 60 round adjustable

trim 2 lamps

048-2622511M 048-2698317 002-90762



Project / Type _____
 Notes _____
 Count / Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF
 MF Maintenance Factor
 LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor
 LLMF Lamp Lumens Maintenance Factor
 LSF Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B16	30
C10	23
C16	36

Components

MOUNTING SET with trim 2 lamps

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
for intermediate ceilings	traffic white	147-80-21	048-2698317



CONVERTER

L-W-H (MM)	ARTICLE NUMBER(S)
143-43-30	002-90762



Mounting accessories

PRIMED CONCRETE MOUNTING HOUSING

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	614-307-120	048-2695110



Optional electrical accessories

DIN RAIL POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



DIN RAIL LED DRIVER

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
DALI-2 200-1050 mA 2 x 42W	36-88-59	005-6121030

