

# SASSO 60 square downlight

trim 2 lamps


048-2612E17F 048-2699318 002-90762



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed  
white , RAL9016 <sup>1</sup>  
Mounting set jet black  
front IP40 , back IP20  
1550 lm

## LED

colour warm dimming  
1800 K - 3000 K  
CRI ≥ 90  
L85 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 101 , R<sub>r</sub>: 94 , R<sub>t(1-5)</sub>: 96  
MR 0.64  
MDER 0.58

## Optical

flood  
beam angle 35°  
UGR < 19  
P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2  
24.0 W  
total insets 20.4 W  
PC2 220-240V  
65 lm/W  
1 DALI Addr.

## Physical


trim  
length 147 mm  
width 81 mm  
height 48 mm  
0.34 kg

## Cutout


length 138 mm  
width 73 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

