

SASSO 60 round downlight

trim 2 lamps

048-2602617S 048-2698318 002-90762



Project / Type

Notes

Count / Date



General

Ceiling , Recessed
 rotation 360°
 white , RAL9016 ¹
 Mounting set jet black
 front IP44 , back IP20
 1210 lm

LED

4000 K
 CRI ≥ 90
 initial MacAdam ≤ 3 SDCM

Optical

spot
 beam angle 11°
 PstLM ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical

DALI-2
 26.2 W
 total insets 22.3 W
 PC2 220-240V
 46 lm/W
 1 DALI Addr.

Physical

trim
 length 147 mm
 width 80 mm
 height 48 mm
 0.34 kg


Cutout

diameter 70 mm
 length 136 mm
 min. ceiling thickness 2 mm
 max. ceiling thickness 25 mm
 recessed depth 110 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 2 lamps; surface white; installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 11° beam; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

