

# SASSO 60 round downlight

trim 2 lamps


048-2602519S 048-269831G 002-90771



Project / Type

Notes

Count / Date



## General

Ceiling , Recessed  
 rotation 360°  
 gold , RAL260-M <sup>1</sup>  
 Mounting set silver-grey  
 front IP44 , back IP20  
 1040 lm

## LED

3000 K  
 CRI ≥ 90  
 initial MacAdam ≤ 3 SDCM

## Optical

spot  
 beam angle 12°  
 UGR < 16 , ≥65° <1500 cd/m<sup>2</sup>  
 PstLM ≤ 1.0 <sup>2</sup>  
 SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM  
 26.2 W  
 total insets 22.3 W  
 PC2 220-240V  
 40 lm/W

## Physical

trim  
 length 147 mm  
 width 80 mm  
 height 48 mm  
 0.28 kg


## Cutout

diameter 70 mm  
 length 136 mm  
 min. ceiling thickness 2 mm  
 max. ceiling thickness 25 mm  
 recessed depth 90 mm


<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 2 lamps; surface gold; installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim silver-grey; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m<sup>2</sup>; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

