

# SASSO 60 round downlight

trim

048-2602417F 048-2696318 002-90762



Project / Type
Notes
Count / Date



↑ IP20 ↓ IP44	220-240V	↻	X-PERT	X-PERT
------------------	----------	---	--------	--------

### General

Ceiling , Recessed
rotation 360°
white , RAL9016 <sup>1</sup>
Mounting set jet black
front IP44 , back IP20
966 lm

### LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.53
MDER 0.48

### Optical

flood
beam angle 46°
UGR < 19 , ≥65° <1500 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2
12.6 W
PC2 220-240V
77 lm/W
1 DALI Addr.

### Physical


trim
diameter 80 mm
height 48 mm
0.27 kg

### Cutout

diameter 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator

