SASSO PRO 100
adjustable offset trim square

048-2413637F 052-1952417

Project / Type

Notes

Count / Date

Round recessed spotlight in die-cast aluminium with recessed luminaire plane; surface traffic white powder coated; 360° rotatable and 35° tiltable; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim traffic white; suitable for ceiling thickness of 5-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality reflector made of plastic with spherical reflector; aluminium, vapour deposition coated; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 39° beam; installed and exchanged without tools; optical attachments available as accessories; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; converter wired secondary side; through wiring connection box, 3-pole or 5-pole, available as an accessory; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



flood 39°

h (m)	E0° (lx)	ø (m)
1	6050	0.71
2	1510	1.42
3	670	2.13
4	380	2.84
5	240	3.54

Product drawing



General

Ceiling | Recessed
tilt max 35°
rotation 360°
traffic white | RAL 9016 [1]
Mounting set traffic white
IP20
2840 lm

LED

4000 K
CRI ≥ 90
L90 / 50000 h
R_g: 97 | R_f: 89 | $R_{f\{1\text{-}15\}}$: 91
MR 0.85 | MDER 0.77

Optical

flood | beam angle 39°
PstLM ≤ 1.0 [2]| SVM ≤ 0.4 [2]

Electrical

DALI-2 | 1 DALI Addr.
PC2 | 220-240 V
system 27.0 W
system 105 lm/W [3]

Physical

trim
length 112 mm | width 112 mm | height 106 mm
0.63 kg

Cutout

diameter 108 mm
min. ceiling thickness 5 mm | max. ceiling thickness 25 mm
recessed depth 130 mm

[1] RAL code [2] Value of containing product at full load (undimmed) [3] incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

Lighting calculator

['048-2413637F 052-1952417'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com