

SASSO PRO 100

adjustable

offset trimless

048-2413618M 052-1931447



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed
tilt max 35°
rotation 360°
black , RAL 9005 ¹
Mounting set traffic white
IP20
2740 lm

LED

4000 K
CRI ≥ 90
L90 / 50000 h
R _g : 97 , R _f : 89 , R _(f-15) : 91
MR 0.85
MDER 0.77

Optical

medium
beam angle 26°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

non DIM
220-240 V
system 27.0 W
system 101 lm/W ³
PC2

Physical


trimless
length 105 mm
width 113 mm
height 106 mm
0.6 kg

Cutout

diameter 116 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 25 mm
recessed depth 130 mm

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses
& operating device efficiency



Light distribution



medium 26°

h (m)	E0° (lx)	ø (m)
1	9440	0.47
2	2360	0.93
3	1050	1.40
4	590	1.86
5	380	2.33

Product drawing



Installation instructions



Lighting calculator

