

SASSO PRO 100

adjustable offset trim square

048-2412538F 052-1952418



Project / Type

Notes

Count / Date



General
Ceiling Recessed
tilt max 35°
rotation 360°
black RAL 9005 ¹
Mounting set jet black
IP20
2220 lm

LED
3000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 100 R _f : 89 R _{f(1-15)} : 89
MR 0.56 MDER 0.51

Optical
flood beam angle 38°
PstLM ≤ 1.0 ² SVM ≤ 0.4 ²


Electrical
DALI-2 1 DALI Addr.
PC2 220-240 V
system 27.0 W
system 82 lm/W ³

Physical
trim
length 112 mm width 112 mm height 106 mm
0.59 kg

Cutout
diameter 108 mm
min. ceiling thickness 5 mm max. ceiling thickness 25 mm
recessed depth 130 mm


¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Light distribution



h (m)	EO° (lx)	ø (m)
1	4970	0.69
2	1240	1.38
3	550	2.07
4	310	2.76
5	200	3.45

Product drawing



Installation instructions



Lighting calculator

