

# SASSO PRO 100

## adjustable offset trim round

048-2413437F 052-1932448



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



220-240V

360° rotation

X-PERT

X-PERT

**General**

Ceiling , Recessed

tilt max 35°

rotation 360°

white , RAL9016 <sup>1</sup>

Mounting set jet black

IP20

2580 lm

**LED**

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 101 , R<sub>r</sub>: 94 , R<sub>{1-15}</sub>: 95

MR 0.55

MDER 0.5

**Optical**

flood

beam angle 39°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

**Electrical**

DALI-2

27.0 W

PC2 220-240V

96 lm/W

1 DALI Addr.

**Physical**

trim

diameter 112 mm

height 106 mm

0.59 kg

**Cutout**


diameter 108 mm

min. ceiling thickness 5 mm

max. ceiling thickness 25 mm

recessed depth 130 mm



### Light distribution



flood 39°

h (m)	E0° (lx)	ø (m)
1	5490	0.71
2	1370	1.42
3	610	2.13
4	340	2.84
5	220	3.54

### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

**Installation instructions**

**Lighting calculator**

QR code for installation instructions

QR code for lighting calculator

