

SASSO PRO 100

adjustable flush trim square

048-2412L37F 052-1942417



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Recessed
 tilt max 35°
 rotation 360°
 white | RAL 9016 ¹
 Mounting set traffic white
 IP20
 1830 lm

LED

tunable white | 1800 K - 3000 K
 CRI ≥ 92
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 101 | R_r: 94 | R_{f(1-5)}: 97
 MR 0.64 | MDER 0.58

Optical

flood | beam angle 38°
 PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical

DALI-2 DT8 | 2 DALI Addr.
 PC2 | 220-240 V
 system 29.7 W
 system 62 lm/W ³

Physical

trim
 length 112 mm | width 112 mm | height 106 mm
 0.62 kg


Cutout

diameter 108 mm
 min. ceiling thickness 5 mm | max. ceiling thickness 25 mm
 recessed depth 110 mm

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Round recessed spotlight in die-cast aluminium; surface white powder coated; 360° rotatable and 35° tiltable; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim traffic white; suitable for ceiling thickness of 5-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour: tunable white diodes (1800-3000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 92; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality reflector made of plastic with spherical reflector; aluminium, vapour deposition coated; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 38° beam; installed and exchanged without tools; optical attachments available as accessories; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 / DT8 converter; converter wired secondary side; through wiring connection box, 3-pole or 5-pole, available as an accessory; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 38°

h (m)	E0° (lx)	ø (m)
1	4010	0.69
2	1000	1.38
3	450	2.07
4	250	2.76
5	160	3.45

Product drawing



Installation instructions



Lighting calculator

