

TWIST 100

trim

048-1120518M 048-2796317 002-90781



Project / Type

Notes

Count / Date



General

LED

Optical

Electrical

Physical

Cutout

Round recessed spotlight in die-cast aluminium; 1 lamp; surface black powder coated; installation without tools in mounting set due to patented ball catch system; suitable for ceiling thickness of 2-25 mm; 360° rotatable and 45° tiltable outward; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 28° beam; optical attachments available as accessories; degree of protection IP20; PC2 220-240V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Installation instructions



Lighting calculator



Light distribution



medium 28°

h (m)	E0° (lx)	ø (m)
1	10600	0.49
2	2700	0.99
3	1200	1.48
4	700	1.97
5	400	2.46

Product drawing



TWIST 100

trim

048-1120518M 048-2796317 002-90781



Project / Type

Notes

Count / Date

Components

MOUNTING SET with trim 1 lamp

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
for intermediate ceilings	traffic white	118	048-2796317

POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
136-43-30	002-90781

Mounting accessories

THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
non DIM cable ø 4 – 12 mm	105-58-30	005-2531110
DALI cable ø 4 – 12 mm	105-58-30	005-2551110

Optical accessories

LINEAR PRISMATIC LENS

Ø (MM)	ARTICLE NUMBER(S)
75	080-6402110P

HONEYCOMB LOUVER

Ø (MM)	ARTICLE NUMBER(S)
75	080-6401118

SNOOT

TYPE	Ø (MM)	ARTICLE NUMBER(S)
short	66	080-6403118
medium	66	080-6403218
angle	66	080-6403318

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	11
B13	15
B16	19
B20	23
C10	19
C13	25
C16	32
C20	39

