TWIST 100 trim 2 lamps

048-1120517S 048-2798318 002-90781



Project / Type

Notes

Count / Date



O-240V X-PERT

General

LED

,,

Optical

Electrical

Physical

Cutout

Installation instructions


Lighting calculator





Round recessed spotlight in die-cast aluminium; 2 lamps; surface white powder coated; installation without tools in mounting set due to patented ball catch system; suitable for ceiling thickness of 2-25 mm; 360° rotatable and 45° tiltable outward; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 17° beam; degree of protection IP20; PC2 220-240V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



spot 17°

h (m)	E0° (Ix)	ø (m)
1	22300	0.30
2	5600	0.60
3	2500	0.90
4	1400	1.19
5	900	1.49

Product drawing









TWIST 100 trim 2 lamps

048-1120517S 048-2798318 002-90781



Project / Type				
Notes				
Count / Date				

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures	
B10	11	
B13	15	
B16	19	
B20	23	
C10	19	
C13	25	
C16	32	
C20	39	

Components

MOUNTING SET with trim 2 lamps

TYPECOLOURL·W·H (MM)ARTICLE NUMBER(S)for intermediate ceilingsjet black218·118·35048-2798318





POWER SUPPLY

L-W-H (MM) ARTICLE NUMBER(S) 136.43.30 002.90721



