

# TWIST 100 trim 2 lamps

048-1120617F 048-2798318 002-90782



Project / Type

Notes

Count / Date



## General

## LED

## Optical

## Electrical

## Physical

## Cutout

Round recessed spotlight in die-cast aluminium; 2 lamps; surface white powder coated; installation without tools in mounting set due to patented ball catch system; suitable for ceiling thickness of 2-25 mm; 360° rotatable and 45° tiltable outward; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 38° beam; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


## Installation instructions



## Lighting calculator




## Light distribution



flood 38°

h (m)	E0° (lx)	ø (m)
1	7220	0.68
2	1810	1.37
3	800	2.05
4	450	2.73
5	290	3.42

## Product drawing



# TWIST 100 trim 2 lamps

048-1120617F 048-2798318 002-90782



Project / Type

Notes

Count / Date

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	37
B16	60
C10	37
C16	60

## Components

### MOUNTING SET with trim 2 lamps

TYPE	COLOUR	L·W·H (MM)	ARTICLE NUMBER(S)
for intermediate ceilings	jet black	218·118·35	048-2798318



### POWER SUPPLY

L·W·H (MM)	ARTICLE NUMBER(S)
143·43·30	002-90782

