


BASO 40 wallwasher suspended

045-122661GA



Project / Type _____
Notes _____
Count / Date _____



General

Ceiling , Suspended _____
grey , RAL9006 ¹ _____
IP20 _____
5450 lm _____

LED

4000 K _____
CRI ≥ 80 _____
L90 / 50000 h _____
photobio. safety RG 0 - no Risk _____
initial MacAdam ≤ 3 SDCM _____
MR 0.72 _____
MDER 0.66 _____

Optical

Asymmetric Wallwasher _____
PstLM ≤ 1.0 ² _____
SVM ≤ 0.4 ² _____

Electrical


non DIM _____
41 W _____
PC1 220-240V _____
133 lm/W _____
23 W/m _____

Physical


cable 1500 mm _____
length 1809 mm _____
width 42 mm _____
height 76 mm _____
3.9 kg _____

Luminaire housing made of extruded aluminium profile; light tight final end caps made of aluminium; no visible screws; angular design; surface grey powder coated; suspended luminaire with 1500mm cable suspension; with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; incl. transparent feed; luminaire profile with pre-assembled converter unit can be pre-mounted on site; remaining lamp components mounted without tools; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetric lens for homogeneous vertical lighting intensity; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

