

MINO 60 CIRCLE 1000

direct / indirect

suspended

034-241353GH



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|------------------------------|--|
| Ceiling , Suspended | |
| grey , RAL 9006 ¹ | |
| IP20 | |
| indirect 3010 lm | |
| direct 6570 lm | |
| total 9580 lm | |

LED

| | |
|--------------------------|--|
| 3000 K | |
| CRI ≥ 80 | |
| L90 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| MR 0.56 | |
| MDER 0.51 | |

Optical

| | |
|---------------------------------------|--|
| High Performance Opal | |
| opal (lambertsch) | |
| PstLM ≤ 1.0 ² ³ | |
| SVM ≤ 0.4 ² ³ | |

Electrical

| | |
|------------------------------|--|
| DALI-2 | |
| 220-240 V | |
| system 71 W | |
| system 135 lm/W ⁴ | |
| PC1 | |
| 5 DALI Addr. | |


Physical

| | |
|--------------------------------|--|
| cable 1500 mm / canopy central | |
| diameter 1060 mm | |
| height 80 mm | |
| centerline radius 500 mm | |
| 9 kg | |


¹ RAL code ² combined
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suspended luminaire with 1500mm cable suspension (canopy central); with integrated toolless suspension height adjustment on the luminaire; incl. feed (white); surface grey powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



*canopy central version

Installation instructions



Lighting calculator

