

CORNER high lumen

surface

040-896351GO



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Surface

grey , RAL9006 ¹

4220 lm/m

IP20

3680 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.54

MDER 0.49

Optical

High Performance Opal

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

30 W

PC1 220-240V

123 lm/W

35 W/m

Physical

length 888 mm

width 65 mm

height 65 mm

1.99 kg


¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Luminaire housing made of extruded aluminium profile; angular design; no visible screws; surface grey powder coated; suitable for wall or ceiling mounting; with two sided light beam; HPO (High Performance Opal) cover for uniform illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; luminaire with 2 cable openings and plug-in terminal for through wiring; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

