

MINO 60 CIRCLE 1500

direct

suspended

034-2410638H



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Suspended _____

black | RAL 9005 ¹ _____

IP20 _____

12000 lm _____

LED

4000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.72 | MDER 0.65 _____

Optical

High Performance Opal | opal (lambertsch) _____

PstLM ≤ 1.0^{2 3} | SVM ≤ 0.4^{2 3} _____

Electrical

DALI-2 | 4 DALI Addr. _____

PC1 | 220-240 V _____

system 83 W _____

system 145 lm/W ⁴ _____

Physical

cable 1500 mm / canopy central _____


diameter 1560 mm | height 80 mm _____

centerline radius 750 mm _____


13 kg _____

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suspended luminaire with 1500mm cable suspension (canopy central); with integrated toolless suspension height adjustment on the luminaire; incl. feed (black); surface black powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² combined
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

