

# MINO 60 CIRCLE 1000

direct / indirect

suspended

034-221363XZ



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

special colours

IP20

indirect 3430 lm

direct 6500 lm

total 9930 lm

## LED

4000 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.72

MDER 0.65

## Optical

Microprismatic

microprismatic

UGR  $\leq 19$

PstLM  $\leq 1.0^{1,2}$

SVM  $\leq 0.4^{1,2}$

## Electrical

DALI-2

220-240 V

system 71 W

system 140 lm/W<sup>3</sup>

PC1

5 DALI Addr.

## Physical

cable 1500 mm

diameter 1060 mm

height 80 mm


centerline radius 500 mm

8 kg


<sup>1</sup> combined <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Light distribution



## Product drawing



[034-221363XZ] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

01.05.2025