

MINO 60 CIRCLE 1500

direct / indirect

suspended

034-2211638Z



Project / Type	
Notes	
Count / Date	



General

Ceiling , Suspended	
black , RAL 9005 ¹	
IP20	
indirect 5490 lm	
direct 10400 lm	
total 15900 lm	

LED

4000 K	
CRI ≥ 80	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
MR 0.72	
MDER 0.65	

Optical

Microprismatic	
microprismatic	
PstLM ≤ 1.0 ² ³	
SVM ≤ 0.4 ² ³	

Electrical

DALI-2	
220-240 V	
system 114 W	
system 139 lm/W ⁴	
PC1	
5 DALI Addr.	


Physical

cable 1500 mm	
diameter 1560 mm	
height 80 mm	
centerline radius 750 mm	
13 kg	


¹ RAL code ² combined
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suspended luminaire with 1500mm cable suspension; with integrated toolless suspension height adjustment on the luminaire; incl. feed (black); surface black powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

