

MINO 60 CIRCLE 1500

direct / indirect

suspended

034-2211538Z



Project / Type _____

Notes _____

Count / Date _____



Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suspended luminaire with 1500mm cable suspension; with integrated toolless suspension height adjustment on the luminaire; incl. feed (black); surface black powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling | Suspended
black | RAL 9005 ¹
IP20
indirect 4820 lm | direct 9130 lm
total 13950 lm

LED

3000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.56 | MDER 0.51

Optical

Microprismatic | microprismatic
UGR ≤ 19
PstLM $\leq 1.0^2$ ³ | SVM $\leq 0.4^2$ ³


Electrical

DALI-2 | 5 DALI Addr.
PC1 | 220-240 V
system 114 W
system 122 lm/W ⁴


Physical

cable 1500 mm
diameter 1560 mm | height 80 mm
centerline radius 750 mm
13 kg

Light distribution



Product drawing



¹ RAL code ² combined
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

