

# MINO 60 CIRCLE 1500

direct / indirect

suspended

034-2211537Z



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Suspended	
white , RAL 9010 <sup>1</sup>	
IP20	
indirect 4820 lm	
direct 9130 lm	
total 13950 lm	

## LED

3000 K	
CRI ≥ 80	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
MR 0.56	
MDER 0.51	

## Optical

Microprismatic	
microprismatic	
UGR ≤ 19	
PstLM ≤ 1.0 <sup>2 3</sup>	
SVM ≤ 0.4 <sup>2 3</sup>	

## Electrical

DALI-2	
220-240 V	
system 114 W	
system 122 lm/W <sup>4</sup>	
PC1	
5 DALI Addr.	


## Physical

cable 1500 mm	
diameter 1560 mm	
height 80 mm	
centerline radius 750 mm	
13 kg	


<sup>1</sup> RAL code <sup>2</sup> combined  
<sup>3</sup> Value of containing product at full load (undimmed)  
<sup>4</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suspended luminaire with 1500mm cable suspension; with integrated toolless suspension height adjustment on the luminaire; incl. feed (white); surface white powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

