

MINO 60 CIRCLE 1500

direct

ceiling

034-2110638Z



Project / Type

Notes

Count / Date



General

Ceiling | Surface

jet black | RAL 9005

IP20

10400 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72 | MDER 0.65

Optical

Microprismatic | microprismatic

PstLM ≤ 1.0^{1 2} | SVM ≤ 0.4^{1 2}

Electrical

DALI-2 | 4 DALI Addr.

PC1 | 220-240 V

system 83 W

system 125 lm/W³

Physical


diameter 1560 mm | height 80 mm

centerline radius 750 mm


12 kg

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suitable for ceiling mounting; surface jet black powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ combined ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

