

MINO 60 CIRCLE 1500

direct

ceiling
034-211053XH



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Surface _____

special colours _____

IP20 _____

10500 lm _____

LED

3000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.56 | MDER 0.51 _____

Optical

High Performance Opal | opal (lambertsch) _____

PstLM ≤ 1.0^{1 2} | SVM ≤ 0.4^{1 2} _____

Electrical

DALI-2 | 4 DALI Addr. _____

PC1 | 220-240 V _____

system 83 W _____

system 127 lm/W³ _____

Physical


diameter 1560 mm | height 80 mm _____

centerline radius 750 mm _____


12 kg _____

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suitable for ceiling mounting; surface special colours powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions

