

MINO 60 CIRCLE 1500

direct

ceiling
034-211053XH



Project / Type _____


Notes _____

Count / Date _____




Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suitable for ceiling mounting; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; internal wiring in light halogen free; incl. converter, non dimmable; sound absorbing accessories available;

Light distribution



Product drawing



General

Ceiling , Surface _____

special colours _____

IP20 _____

10500 lm _____

LED

3000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

MR 0.56 _____

MDER 0.51 _____

Optical

High Performance Opal _____

PstLM ≤ 1.0 ¹ _____

SVM ≤ 0.4 ¹ _____

Electrical

DALI-2 _____

88 W _____

PC1 220-240V _____

119 lm/W _____

4 DALI Addr. _____

Physical

diameter 1560 mm _____

height 80 mm _____

centerline radius 750 mm _____

12 kg _____

¹ Value of containing product at full load (undimmed)

Lighting calculator

