

# MINO CIRCLE ACOUSTIC

## 1500

ceiling  
034-271211W



Project / Type	
Notes	
Count / Date	



<b>General</b>
Ceiling , Surface
white

<b>Physical</b>
diameter 1434 mm
height 24 mm
8.4 kg

<b>Acoustics</b>
Alpha w ( $\alpha_w$ ) up to 0.7 <sup>1</sup>
SAC (sound absorption class) up to C <sup>1</sup>
NRC up to 1.15 <sup>1</sup>
SAA up to 1.16 <sup>1</sup>


<sup>1</sup> Acoustic data calculations based on MINO CIRCLE ACOUSTIC 1000, cavity 3cm

### Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, white; colour may deviate; absorption of direct sound; this creates high acoustic performance; for ceiling surface mounting;

### Product drawing



# MINO CIRCLE ACOUSTIC 1500

ceiling  
034-271211W



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.3	0.6	1.43	2.3	2.17	2.1

## Sound absorption coefficient ( $\alpha_p$ )

