

# MINO CIRCLE ACOUSTIC 1500

inlay  
034-270211W



Project / Type

Notes

Count / Date



General

Luminaire / Track | Mounted

white

Physical

diameter 1434 mm | height 24 mm

9.4 kg

Acoustics

Alpha w ( $\alpha_w$ ) up to 0.65<sup>1</sup>

SAC (sound absorption class) up to C<sup>1</sup>

NRC up to 0.7<sup>1</sup>

SAA up to 0.74<sup>1</sup>


<sup>1</sup> Acoustic data calculations based on MINO CIRCLE ACOUSTIC 1000, cavity 100cm

## Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, white; colour may deviate; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for insertion into the MINO 60 CIRCLE 1500 ceiling or MINO 60 CIRCLE 1500 suspended;

## Product drawing



# MINO CIRCLE ACOUSTIC 1500

inlay  
034-270211W



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.97	1.2	1.83	2.67	3.07	3.3

## Sound absorption coefficient ( $\alpha_p$ )

