

MINO 60 CIRCLE 1000

direct / indirect

suspended
034-241363XH



Project / Type
Notes
Count / Date



General

Ceiling , Suspended
special colours
IP20
indirect 3430 lm
direct 7480 lm
total 10910 lm

LED

4000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.72
MDER 0.65

Optical

High Performance Opal
opal (lambertsch)
PstLM $\leq 1.0^{1,2}$
SVM $\leq 0.4^{1,2}$

Electrical

DALI-2
220-240 V
system 71 W
system 154 lm/W ³
PC1
5 DALI Addr.


Physical

cable 1500 mm / canopy central
diameter 1060 mm
height 80 mm
centerline radius 500 mm
9 kg


¹ combined ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suspended luminaire with 1500mm cable suspension (canopy central); with integrated toolless suspension height adjustment on the luminaire; incl. feed (white); surface special colours powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



*canopy central version

Installation instructions



Lighting calculator

