

TUBO 100

system

029-8832617 029-00667 006-5205700



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL9010 ¹

4420 lm/m

IP20

2520 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

Optical

High Performance Opal

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

no emergency light

18.3 W

PC1 220-240V

138 lm/W

32 W/m

Physical

length 582 mm


width 100 mm

height 100 mm


1.38 kg

Carrier profile made of extruded aluminium profile; light tight final end caps made of aluminium (available as an accessory); no visible screws; for continuous lighting systems; surface white powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; spring clip attachment to the luminaire; freely positionable; lighting profile (end cover pre-assembled) available in advance for installation; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; cylindrical cover made of satin PMMA for uniform illumination; with 340° light emission and gentle ceiling illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator



TUBO 100

system

029-8832617 029-00667 006-5205700



Project / Type	
Notes	
Count / Date	

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.91	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a Room Surface Maintenance Factor		
MF	Maintenance Factor		LLMF Lamp Lumens Maintenance Factor		
LMF ^a	Luminaire Maintenance Factor		LSF Lamp Survival Faktor		

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	23
B13	30
B16	36
B20	46
C10	35
C13	50
C16	60
C20	76

Components

INSTALLATION CHANNEL

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
582 mm	582-68-29	029-00667



COVER OPAL

TYPE	Ø (MM)	ARTICLE NUMBER(S)
577 mm	100	006-5205700



Mounting accessories

END CAPS

TYPE	Ø (MM)	ARTICLE NUMBER(S)
1 pair	104	029-14067



LINEAR CONNECTOR

TYPE	ARTICLE NUMBER(S)
1 piece	029-12027
10 pieces	029-1202710



OPAL COVER LINEAR CONNECTOR

ARTICLE NUMBER(S)
029-12927



ANTI-SLIP PROTECTION

TYPE	ARTICLE NUMBER(S)
per cover	029-00347



TUBO 100

system

029-8832617 029-00667 006-5205700



Project / Type

Notes

Count / Date

Mounting accessories

MOUNTING SET

ARTICLE NUMBER(S)	
029-00446	



CABLE SUSPENSION

TYPE	ARTICLE NUMBER(S)
straight	005-2142110
angular max. 60°	005-2142210



CANOPY / FEEDER CABLE

TYPE	ARTICLE NUMBER(S)
3 x 1,5 mm ²	005-2222317
5 x 1,5 mm ²	005-2222417



CABLE RAIL

Ø (MM)	ARTICLE NUMBER(S)
1200	005-2491110



Electrical accessories

THROUGH WIRE

TYPE	ARTICLE NUMBER(S)
3 x 1,5 mm ² 10 pieces	004-90003
5 x 1,5 mm ² 10 pieces	004-90005

