

# PABLO multilens

180-5710587



Project / Type

Notes

Count / Date



Track light made of die-cast aluminium; surface white powder coated; 360° rotatable and 310° tiltable; converter installed in aluminium spotlight housing; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. exchangeable additional lenses; precise radiation characteristics with different beam angles; optical filter available as accessory; degree of protection IP20; PC1; 220-240 V; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation by means of set screw; incl. converter, dimmable with integrated potentiometer; point outlet, either in surface mounted housing or recessed housing, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



## General

Ceiling | Track

tilt max 310°

rotation 360°

white | RAL 9016 <sup>1</sup>

IP20

890<sup>2</sup>, 911<sup>3</sup>, 961<sup>4</sup>, 981<sup>5</sup>, 1010<sup>6</sup>, 1010<sup>7</sup> lm

## LED

3000 K

CRI  $\geq 90$

L85 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 98 | R<sub>f</sub>: 91 | R<sub>(f-15)</sub>: 89

MR 0.6 | MDER 0.55

## Optical

wide flood<sup>2</sup>, medium<sup>3</sup>, flood<sup>4</sup>, flood<sup>5</sup>, spot<sup>6</sup>, super spot<sup>7</sup> | beam angle 64°<sup>2</sup>, 30°<sup>3</sup>, 38°<sup>4</sup>, 40°<sup>5</sup>, 19°<sup>6</sup>, 10°<sup>7</sup>

PstLM  $\leq 1.0$ <sup>2 4 6 5 3 7 8</sup> | SVM  $\leq 0.4$ <sup>2 4 6 5 3 7 8</sup>

## Electrical

DIM POT1

PC1 | 220-240 V

system 14.7 W

system 61<sup>2</sup>, 62<sup>3</sup>, 65<sup>4</sup>, 67<sup>5</sup>, 69<sup>6</sup>, 69<sup>7</sup> lm/W <sup>9</sup>

## Physical

diameter 70 mm | height 98 mm

0.92 kg

set screw (tool required)

<sup>1</sup> RAL code <sup>2</sup> 64 degrees <sup>3</sup> 30 degrees <sup>4</sup> 38 degrees  
<sup>5</sup> 40 degrees <sup>6</sup> 19 degrees <sup>7</sup> 10 degrees  
<sup>8</sup> Value of containing product at full load (undimmed)  
<sup>9</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



## Lighting calculator





Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

Light distribution



Product drawing



super spot 10°

h (m)	E0° (lx)	ø (m)
1	23700	0.18
2	5900	0.36
3	2600	0.53
4	1500	0.71
5	900	0.89

spot 19°

h (m)	E0° (lx)	ø (m)
1	6160	0.33
2	1540	0.65
3	680	0.98
4	390	1.31
5	250	1.63

medium 30°

h (m)	E0° (lx)	ø (m)
1	2070	0.54
2	520	1.08
3	230	1.63
4	130	2.17
5	80	2.71

flood 38°

h (m)	E0° (lx)	ø (m)
1	1710	0.69
2	430	1.37
3	190	2.06
4	110	2.75
5	70	3.43

flood 40°

h (m)	E0° (lx)	ø (m)
1	1750	0.72
2	440	1.44
3	190	2.16
4	110	2.88
5	70	3.60

wide flood 64°

h (m)	E0° (lx)	ø (m)
1	735	1.24
2	184	2.48
3	82	3.72
4	46	4.96
5	29	6.19

# PABLO multilens

180-5710587



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup> Room Surface Maintenance Factor		
MF	Maintenance Factor		LLMF Lamp Lumens Maintenance Factor		
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF Lamp Survival Factor		

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	31
B13	40
B16	50
B20	62
B25	78
C10	52
C13	67
C16	85
C20	104
C25	130

## Mounting accessories

### RECESSED HOUSING

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
point outlet	traffic white	151	186-072277
point outlet	jet black	151	186-072278



### SURFACE HOUSING

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
point outlet	traffic white	120	186-072287
point outlet	jet black	120	186-072288



## Optical accessories

### OVAL FILTER

TYPE	ARTICLE NUMBER(S)
60 x 15°	080-5900020



## Other accessories

### DIFFUSION SHEET FOR SUPERSPOT

TYPE	ARTICLE NUMBER(S)
for a better homogeneous illumination	080-5900030

