

L4

MOVE IT 45

090-9L453WB001




Project / Type	
Notes	
Count / Date	




Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; equipped with four wallwasher floor light elements; asymmetrical light distribution with precise radiation characteristic; high quality reflector with micro-faceted, aluminum-vaporised surface; Reflector chrome; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable; NOT suitable for MOVE IT 45 set;

Light distribution



Product drawing



General

Ceiling Track	
black RAL 9005 ¹	
Reflector chrome	
IP20	
1240 lm	
optical inset 108 lm/W ²	

LED

3000 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 100 R _f : 92 R _{t(1-5)} : 91	
MR 0.64 MDER 0.58	

Optical

wallwasher floor	
PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³	

Electrical

DALI-2 1 DALI Addr.	
PC3 48 V	
fixture 13.6 W	
optical inset 11.5 W	

Physical

length 156 mm width 43 mm height 48 mm	
0.4 kg	

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

