


## Quickinfo

2700 K, 3000 K, 4000 K  
 CRI ≥ 90, 3 SDCM  
 up to 95 lm/W  
 L90 @ 50 000 h  
 non DIM, DALI-2

## Types



## Colours



## Light distributions



DESIGN  
AWARD  
2020




reddot winner 2020

# ARY rod


suspended

**EN** Decorative suspended luminaire in aluminium; surface powder coated; height adjustable U-profile pendant rod suspension (black or white), feed in U-profile; spotlight head either fixed or 265° rotatable and 90° tiltable; good glare reduction due to recessed light point plane; incl. high quality lens system; precise radiation characteristics with different beam angles; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory


**DE** Dekorative Pendelleuchte aus Aluminium; Oberfläche pulverbeschichtet; kürzbare U-Profil-Pendelstangenabhängung (schwarz oder weiß), Einspeiseleitung in U-Profil; Strahlerkopf wahlweise starr bzw. 265° dreh- und 90° schwenkbar; gute Entblendung durch zurückversetzte Lichtpunktebene; inkl. hochwertiger Linsenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; mit COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung; Konverter im Baldachin enthalten; Deckenmontageringe für multiple Positionierung der Leuchte im Raum als Zubehör erhältlich



265° rotatable,  
90° tiltable



free positioning by  
ring and hook



track version  
available (p. 734)

## Order options

### MOUNTING

- suspension 1500 mm 1  
suspension 2000 mm with hook\* 2

\*one ring included

### COLOUR TEMPERATURE

- 2700 K 4  
3000 K 5  
4000 K 6

### MATERIAL COLOUR

- traffic white RAL 9016 7  
● jet black RAL 9005 8  
special colours\* p. 992 X

\*rod always in white





### ACCESSORY COLOUR

- traffic white RAL 9016 7  
● jet black RAL 9005 8

### BEAM ANGLE

- medium 25° M  
flood 44° F

**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for 3000 K, CRI ≥ 90, colour white, lens flood 2700 K -5%, 4000 K +5%



## ARY rod suspended



### DOWNLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.4 W 18 Vf 500 mA	791 lm	0 4 9 - 5 2 1 1 1 1

## ARY adjustable rod suspended



### SPOTLIGHT ADJUSTABLE

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.4 W 18 Vf 500 mA	791 lm	0 4 9 - 5 3 1 1 1 1

## Mounting accessories

### CANOPY CEILING 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA   non DIM	η 79 %	115-29	0 0 5 - 2 6 0 1 1 1
500 mA   DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 1 1 3

use for suspension with rod

### CANOPY CEILING 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA   non DIM	η 79 %	115-29	0 0 5 - 2 6 0 2 1 1
500 mA   DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 2 1 3

use for suspension with hook

### MOUNTING SET WITH TRIM for installation in ceilings from 2-25 mm

TYPE	Ø-H (mm)	ORDER CODE
single luminaire rod	77-49	0 0 5 - 3 5 2 2 0 1
single luminaire cable*	77-49	0 0 5 - 3 5 2 1 0 1

\*use for suspension with hook

### MOUNTING SET TRIMLESS for installation in plasterboard ceilings 9-25 mm

TYPE	Ø-H (mm)	ORDER CODE
single luminaire rod	75-48	0 0 5 - 3 5 1 2 0 1 7
single luminaire cable*	75-48	0 0 5 - 3 5 1 1 0 1 7

\*use for suspension with hook

### SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting set trimless

### RING

TYPE	Ø-H (mm)	ORDER CODE
ceiling mounted	50-88	0 5 0 - 0 5 1 0 2 1

## Electrical accessories

### POWER SUPPLY 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
500 mA   non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 3 2
500 mA   DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 3 3

### DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W   48 V DC constant voltage	72-90-63	0 0 5 - 6 5 2 0 2 1 0
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current	36-88-59	0 0 5 - 6 1 2 1 0 3 0
2x 42 W   48 V DC   U <sub>OUT</sub> 10-40 V		


for more details and components see page 981



## Quickinfo

2700 K, 3000 K, 4000 K  
CRI ≥ 90, 3 SDCM  
up to 95 lm/W  
L90 @ 50 000 h  
non DIM, DALI-2

## Types



## Colours



## Light distributions



DESIGN  
AWARD  
2020




reddot winner 2020

# ARY cable


suspended

**EN** Decorative suspended luminaire in aluminium; surface powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; good glare reduction due to recessed light point plane; high quality lens system; precise radiation characteristics with different beam angles; shades as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

**DE** Dekorative Pendelleuchte aus Aluminium; Oberfläche pulverbeschichtet; abgependelt mit Pendelabhängung, inkl. Einspeiseleitung (schwarz oder weiß); beliebig kürzbar; gute Entblendung durch zurückversetzte Lichtpunktenebene; hochwertige Linsenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; Shades in den RAL Farben velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white oder signal black als Zubehör; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung; Konverter im Baldachin enthalten; Deckenmontageringe für multiple Positionierung der Leuchte im Raum als Zubehör erhältlich



free positioning by  
ring and hook



track version  
available (p. 736)

