




Quickinfo

6500 K
DALI-2 ESSENTIAL sensor, DALI-2
SENSE sensor
front IP20, IP40, back IP20

Types



Colour



Mounting set



SASSO 60 round sensor / emergency

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement

DE Runder Einsatz (Notlicht bzw. Sensor); werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand); Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; LED Notlicht-Einsatz: 3 Varianten mit verschiedenen Testmöglichkeiten - Basic mit Prüftaste, Selbsttest mit Status-LED oder Pro DALI mit Überwachung über DALI; Sensor mit DALI-2 Steuerung: 2 Varianten - Basic mit Helligkeits- und Anwesenheitssensor oder Pro mit zusätzlicher Temperatur-, Luftfeuchtigkeits-, Luftqualitäts- und Lärmpegelmessung



SASSO 60 round sensor essential

360°

220-240 V


DALI
1 ADDR.

IP20
IP40

presence

brightness

COLOUR	ORDER CODE
jet black	0 4 8 - 2 6 9 3 1 1 1
traffic white	0 4 8 - 2 6 9 3 1 1 7



SASSO 60 round sensor sense

360°

220-240 V

DALI
1 ADDR.

IP20
IP40

brightness

presence



temp.

sound pr.

CO₂

humidity

COLOUR	ORDER CODE
jet black	0 4 8 - 2 6 9 3 1 2 1
traffic white	0 4 8 - 2 6 9 3 1 2 7



SASSO 60 round emergency light

360°


CRI
≥ 80

220-240 V

3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
1.0 W	6500 K	217 lm	0 4 8 - 2 6 9 3 2 1 ☒

incl. 3 interchangeable lenses



3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
1.0 W	6500 K	217 lm	0 4 8 - 2 6 9 3 2 2 ☒

incl. 3 interchangeable lenses

3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
1.0 W	6500 K	217 lm	0 4 8 - 2 6 9 3 2 3 ☒

incl. 3 interchangeable lenses


Order options

COLOUR	☒
jet black RAL 9005	1
traffic white RAL 9016	7


Mounting accessories (required)

		MOUNTING SET trimless			
		TYPE	COLOUR	Ø·H (mm)	ORDER CODE
		for plasterboard ceilings 12.5/15/25 mm	traffic white	73·29	0 4 8 - 2 6 9 6 1 1 7
		for SASSO 60 round SPIO 60 downlight			
		MOUNTING SET trimless for soft acoustic ceilings			
		COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
		traffic white	25-40 mm	80·25	0 4 8 - 2 6 9 6 1 9 7
		MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm			
		COLOUR		Ø·H (mm)	ORDER CODE
		traffic white		80·40	0 4 8 - 2 6 9 6 3 1 7
		jet black		80·40	0 4 8 - 2 6 9 6 3 1 8
		MOUNTING SET with trim for soft acoustic ceilings 25-40 mm			
		COLOUR		Ø·H (mm)	ORDER CODE
		traffic white		80·27	0 4 8 - 2 6 9 6 3 9 7
		jet black		80·27	0 4 8 - 2 6 9 6 3 9 8

Mounting accessories (optional)

	EXPOSED CONCRETE MOUNTING HOUSING			
COLOUR white aluminium	L-W-H (mm) 230-230-162		ORDER CODE 0 4 8 - 2 6 9 5 2 1 0	

	MOUNTING TOOL			
TYPE for soft acoustic ceilings	COLOUR traffic black	L-W-H (mm) 77-77-35	ORDER CODE 0 4 8 - 2 6 9 5 9 1 8	

	PRIMED CONCRETE MOUNTING HOUSING			
L-W-H (mm) 614-307-120	ORDER CODE 0 4 8 - 2 6 9 5 1 1 0			
order mounting set separately				

Electrical accessories (optional)

REPLACEMENT ACCUPACK

TYPE	ORDER CODE
3h battery life	0 4 8 - 2 6 9 3 9 1 0