



BASO 60 IP54

trim


EN Luminaire housing made of extruded aluminium; recessed luminaire with trim; suitable for ceiling thickness of 8-20 mm; surface powder coated; suitable for wall or ceiling mounting; luminaire profile (end caps come pre-assembled) can be pre-mounted; remaining luminaire components mounted without tools; closed light insert made of PMMA, consisting of converter unit and circuit board unit; light inset with screwed-on, thus maintenance-friendly, transparent end cap in PMMA; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering; IP67 socket connector system for easy and sealed electrical connection

DE Leuchtenkörper aus Aluminiumstrangpressprofil; Einbauleuchte mit umlaufendem Rand; geeignet für Deckenstärken von 8-20 mm; Oberfläche pulverbeschichtet; geeignet für Wand- oder Deckenmontage; Leuchtenprofil (Enddeckel werkseitig vormontiert) vorab montierbar; restliche Leuchtenkomponenten werkzeuglos montierbar; geschlossener Lichteinsatz aus PMMA, bestehend aus Konvertereinheit und Platineinheit; Lichteinsatz mit verschraubtem, dadurch wartungsfreundlichen, transparenten PMMA Enddeckel; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; IP67-Buchsen-Steckersystem für dichten elektrischen Anschluss

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
up to 2,340 lm/m
up to 130 lm/W
L90 / 50000 h
DALI-2
High Performance Opal
IP54

Types




Colour



Light distributions




quick
installation



system solution



dust & splash
water
protection (IP
54)



CRI $\geq$ 98
XPECTRUM
(optional)




BASO 60 IP54 trim



OPAL DALI-2, CRI ≥ 80

65xL-10 100



SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	619 mm	3000 K	1320 lm	122 lm/W	8 4 5 - 3 5 2 2 5 3 ☒ H
		4000 K	1400 lm	130 lm/W	8 4 5 - 3 5 2 2 6 3 ☒ H
21.5 W	1219 mm	3000 K	2640 lm	123 lm/W	8 4 5 - 3 5 2 4 5 3 ☒ H
		4000 K	2800 lm	130 lm/W	8 4 5 - 3 5 2 4 6 3 ☒ H
28.7 W	1619 mm	3000 K	3520 lm	123 lm/W	8 4 5 - 3 5 2 5 5 3 ☒ H
		4000 K	3730 lm	130 lm/W	8 4 5 - 3 5 2 5 6 3 ☒ H
43.0 W	2419 mm	3000 K	5280 lm	123 lm/W	8 4 5 - 3 5 2 8 5 3 ☒ H
		4000 K	5600 lm	130 lm/W	8 4 5 - 3 5 2 8 6 3 ☒ H

Mounting accessories (optional)

CONCRETE INSTALLATION HOUSING

L·W·H (mm)	ORDER CODE
662·75·88	0 4 5 - 3 5 9 2 0 1 0
1262·75·88	0 4 5 - 3 5 9 4 0 1 0
1662·75·88	0 4 5 - 3 5 9 5 0 1 0
2462·75·88	0 4 5 - 3 5 9 8 0 1 0

Order options

COLOUR

traffic white RAL 9016

umbra grey RAL 7022



7

D