

# SONIC ABSORBER DISC

suspended  
059-772221W



Project / Type	
Notes	
Count / Date	



<b>General</b>
Ceiling , Suspended
white

<b>Physical</b>
diameter 1050 mm
height 50 mm

<b>Acoustics</b>
Alpha w ( $\alpha_w$ ) up to 0.55 <sup>1</sup>
SAC (sound absorption class) up to D <sup>1</sup>
NRC up to 0.8 <sup>1</sup>
SAA up to 0.82 <sup>1</sup>


<sup>1</sup> Acoustic data calculations based on SONIC ACOUSTIC ABSORBER ring 1280, cavity 180cm

## Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, white; colour may deviate; high acoustic performance by doubling the material; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

## Product drawing



# SONIC ABSORBER DISC

suspended  
059-772221W



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.04	0.45	1.21	1.97	2.04	1.95

## Sound absorption coefficient ( $a_p$ )

