

**LINEA** inner corner opal /  
opal  
wall system  
058-6111638AH



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



<b>General</b>
Ceiling , Suspended
black , RAL9005 <sup>1</sup>
3210 lm/m
IP20
indirect 1940 lm
direct 1940 lm
total 3880 lm


<b>LED</b>
4000 K
CRI ≥ 90
L85 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 98 , R <sub>r</sub> : 90 , R <sub>t[1-15]</sub> : 88
MR 0.76
MDER 0.69

<b>Optical</b>
High Performance Opal
P <sub>stLM</sub> ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


Light fitting and front cover made of extruded aluminium profile; angular design; 90° corner element - inner corner; for lighting systems; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

<b>Electrical</b>
DALI-2
35 W
PC1 220-240V
111 lm/W
29 W/m

**Light distribution**



**Product drawing**



<b>Physical</b>
length 633 mm
width 633 mm
height 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

**Installation instructions**



**Lighting calculator**

