

LINEA inner corner opal / opal
wall system
058-6111537AH



Project / Type _____

Notes _____

Count / Date _____



General
Ceiling , Suspended
white , RAL9010 ¹
2910 lm/m
IP20
indirect 1760 lm
direct 1760 lm
total 3520 lm


LED
3000 K
CRI ≥ 90
L85 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _f : 91 , R _{f-15} : 89
MR 0.61
MDER 0.55

Optical
High Performance Opal
P _{stLM} ≤ 1.0 ²
SVM ≤ 0.4 ²


Light fitting and front cover made of extruded aluminium profile; angular design; 90° corner element - inner corner; for lighting systems; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical
DALI-2
35 W
PC1 220-240V
101 lm/W
29 W/m

Light distribution



Product drawing



Physical
length 633 mm
width 633 mm
height 100 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

