

TASK

table base plate

059-2811178O 059-2891118



Project / Type

Notes

Count / Date



General

Table | Standing

tilt min -15°

tilt max 15°

rotation 360°

black | RAL 9005 ¹

Mounting jet black

IP20

1010 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 | R_r: 90 | R_{t(1-15)}: 87

MR 0.75 | MDER 0.68

Optical

Opal | opal (lambertsch)

Electrical

presence

touch DIM / stand alone sensor

PC2 | 220-240 V

system 11.0 W

system 92 lm/W ²

Physical


base plate

length 227 mm | width 120 mm | height 880 mm


5 kg

Desk lamp in puristic design, with rectangular lamp head with rounded edges in aluminium; extremely flat design (only 15mm); lamp head 360° rotatable and +/- 15° tiltable; lamp arm with 3 joints for maximum flexibility; surface black powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; opal PMMA cover; completely homogeneous illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; continuously adjustable dimming via optical sensor (10-100% analog); presence detector; integrated USB charging socket for charging of a smart device; external power supply for converter with power plug; incl. base plate; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



TASK

table base plate
059-2811178O 059-2891118



Project / Type

Notes

Count / Date

Components

BASE PLATE

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	220	059-2891118

