

TASK

table base plate
059-28110770 059-2891117



Project / Type

Notes

Count / Date



General
Table Standing
tilt min -15°
tilt max 15°
rotation 360°
white RAL 9010 ¹
Mounting pure white
IP20
950 lm

LED
3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 96 R _r : 90 R _{t(1-15)} : 89
MR 0.61 MDER 0.56


Optical
Opal opal (lambertsch)

Electrical
presence
touch DIM / stand alone sensor
PC2 220-240 V
system 11.0 W
system 86 lm/W ²


Physical
base plate
length 227 mm width 120 mm height 880 mm
5.3 kg

Desk lamp in puristic design, with rectangular lamp head with rounded edges in aluminium; extremely flat design (only 15mm); lamp head 360° rotatable and +/- 15° tiltable; lamp arm with 3 joints for maximum flexibility; surface white powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; opal PMMA cover; completely homogeneous illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; continuously adjustable dimming via optical sensor (10-100% analog); presence detector; integrated USB charging socket for charging of a smart device; external power supply for converter with power plug; incl. base plate; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



TASK

table base plate
059-28110770 059-2891117



Project / Type

Notes

Count / Date

Components

BASE PLATE

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
pure white	220	059-2891117

