

# SASSO 60 round wallwasher/floor

trimless exposed concrete

048-2641614W 048-2695210 002-90762



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed  
rotation 360°  
matt silver  
IP20  
805 lm

## LED

4000 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 94 , R<sub>r</sub>: 87 , R<sub>r(1-15)</sub>: 86  
MR 0.8  
MDER 0.72

## Optical

wallwasher floor  
P<sub>stLM</sub> ≤ 1.0<sup>1</sup>  
SVM ≤ 0.4<sup>1</sup>

## Electrical

DALI-2  
9.7 W  
PC2 220-240V  
83 lm/W  
1 DALI Addr.

## Physical

trimless  
length 230 mm  
width 230 mm  
height 162 mm  
2.41 kg


## Cutout

recessed depth 120 mm


<sup>1</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

