

SASSO 60 round adjustable

trimless exposed concrete


048-2622619S 048-2695210 002-90762



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed
 tilt max 30°
 rotation 360°
 gold , RAL260-M ¹
 front IP40 , back IP20
 549 lm

LED

4000 K
 CRI ≥ 90
 initial MacAdam ≤ 3 SDCM

Optical

spot
 beam angle 12°
 UGR < 16 , ≥65° <1500 cd/m²
 PstLM ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical

DALI-2
 13.1 W
 PC2 220-240V
 42 lm/W
 1 DALI Addr.

Physical

trimless
 length 230 mm
 width 230 mm
 height 162 mm
 2.41 kg


Cutout

recessed depth 120 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 60 round adjustable

trimless exposed concrete

048-2622619S 048-2695210 002-90762



Project / Type _____

Notes _____

Count / Date _____

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B16	30
C10	23
C16	36

Components

EXPOSED CONCRETE MOUNTING HOUSING

COLOUR white aluminium L-W-H (MM) 230-230-162 ARTICLE NUMBER(S) 048-2695210



CONVERTER

L-W-H (MM) 143-43-30 ARTICLE NUMBER(S) 002-90762



Optional electrical accessories

DIN RAIL POWER SUPPLY

L-W-H (MM) 72-90-63 ARTICLE NUMBER(S) 005-6520210



DIN RAIL LED DRIVER

TYPE DALI-2 | 200-1050 mA | 2 x 42W L-W-H (MM) 36-88-59 ARTICLE NUMBER(S) 005-6121030

