

# SASSO 60 round adjustable

trimless exposed concrete

048-2622414S 048-2695210 002-90762



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed  
 tilt max 30°  
 rotation 360°  
 matt silver  
 front IP40 , back IP20  
 567 lm

## LED

2700 K  
 CRI ≥ 90  
 initial MacAdam ≤ 3 SDCM  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89  
 MR 0.53  
 MDER 0.48

## Optical

spot  
 beam angle 12°  
 UGR < 16 , ≥65° <1500 cd/m²  
 PstLM ≤ 1.0 <sup>1</sup>  
 SVM ≤ 0.4 <sup>1</sup>

## Electrical

DALI-2  
 13.1 W  
 PC2 220-240V  
 43 lm/W  
 1 DALI Addr.

## Physical

trimless  
 length 230 mm  
 width 230 mm  
 height 162 mm  
 2.41 kg


## Cutout

recessed depth 120 mm


<sup>1</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

