

TASK table table-clamp

059-28111780 059-2892118



Project / Type

Notes

Count / Date




General
Table , Standing
tilt min -15°
tilt max 15°
rotation 360°
black , RAL9005 ¹
Mounting jet black
IP20
1010 lm

LED
4000 K
CRI ≥ 90
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
R _g : 96 , R _f : 90 , R _{i(1-15)} : 87
MR 0.75
MDER 0.68


Optical
Opal

Desk lamp in puristic design, with rectangular lamp head with rounded edges in aluminium; extremely flat design (only 15mm); lamp head 360° rotatable and +/- 15° tiltable; lamp arm with 3 joints for maximum flexibility; surface black powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; opal PMMA cover; completely homogeneous illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; continuously adjustable dimming via optical sensor (10-100% analog); presence detector; integrated USB charging socket for charging of a smart device; external power supply for converter with power plug; incl. table clamp; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical
touch DIM & movement sensor
11.0 W
PC2 220-240V
92 lm/W

Physical
table-clamp
length 227 mm
width 120 mm
height 880 mm
1.3 kg

Cutout
diameter 68 mm

¹ RAL code

Installation instructions



TASK table table-clamp

059-2811178O 059-2892118



Project / Type

Notes

Count / Date

Components

TABLE CLAMP

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
for hole ø 68 mm	jet black	75	059-2892118

