

TASK table table-clamp

059-28111780 059-2892118



Project / Type

Notes

Count / Date



General

Table , Standing

tilt min -15°

tilt max 15°

rotation 360°

black , RAL9005 ¹

Mounting jet black

IP20

1010 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 96 , R_f: 90 , R_{i-15}: 87

MR 0.75

MDER 0.68

Optical

Opal

Electrical

touch DIM & movement sensor

11.0 W

PC2 220-240V

92 lm/W

Physical

table-clamp

length 227 mm

width 120 mm

height 880 mm

1.3 kg

Cutout

diameter 68 mm


¹ RAL code

Installation instructions



Desk lamp in puristic design, with rectangular lamp head with rounded edges in aluminium; extremely flat design (only 15mm); lamp head 360° rotatable and +/- 15° tiltable; lamp arm with 3 joints for maximum flexibility; surface black powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; opal PMMA cover; completely homogeneous illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; continuously adjustable dimming via optical sensor (10-100% analog); presence detector; integrated USB charging socket for charging of a smart device; external power supply for converter with power plug; incl. table clamp; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing

