

INO 900 circle acoustic

luminaire mounted
034-370311X



Project / Type

Notes

Count / Date



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, acoustic special colours; colour may deviate; for mounting on the INO circle suspended cable suspensions, above the luminaire; subsequent attachment possible;

General

Luminaire / Track | Mounted

acoustic special colours

Physical

diameter 794 mm | height 9 mm

1.06 kg

Acoustics

Alpha w (α_w) up to 0.6 ¹

SAC (sound absorption class) up to C ¹

NRC up to 0.55 ¹

SAA up to 0.57 ¹

Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle, cavity 100cm

¹ Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle, cavity 100cm

Installation instructions



INO 900 circle acoustic

luminaire mounted
034-370311X



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.3	0.27	0.47	0.53	0.63	0.8

Sound absorption coefficient (α_p)

