## INO 900 circle acoustic

luminaire mounted 034-370311W



Project / Type

Notes Count / Date

#### General

Luminaire / Track   Mounted	
white	_

#### Physical

diameter 794 mm | height 9 mm 0.84 kg

#### Acoustics

Alpha w ( $\alpha_w$ ) up to 0.6 <sup>1</sup>
SAC (sound absorption class) up to C <sup>1</sup>
NRC up to 0.55 <sup>1</sup>
SAA up to 0.57 <sup>1</sup>
Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle. cavity 100cm

<sup>1</sup> Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle, cavity 100cm

Installation instructions





Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, white; colour may deviate; for mounting on the INO circle suspended cable suspensions, above the luminaire; subsequent attachment possible;



# INO 900 circle acoustic

luminaire mounted 034-370311W



Project / Type

Notes

Count / Date

### Equivalent sound absorption area (A<sub>eq</sub>)

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.3	0.27	0.47	0.53	0.63	0.8

### Sound absorption coefficient (ap)



