

# INO 700 circle acoustic

luminaire mounted  
034-370211D



Project / Type

Notes

Count / Date



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, marble grey; colour may deviate; for mounting on the INO circle suspended cable suspensions, above the luminaire; subsequent attachment possible;

General

Luminaire / Track | Mounted

marble grey

Physical

diameter 648 mm | height 9 mm

0.94 kg

Acoustics

Alpha w ( $\alpha_w$ ) up to 0.6 <sup>1</sup>

SAC (sound absorption class) up to C <sup>1</sup>

NRC up to 0.55 <sup>1</sup>

SAA up to 0.57 <sup>1</sup>

Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle, cavity 100cm

<sup>1</sup> Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle, cavity 100cm

## Installation instructions



# INO 700 circle acoustic

luminaire mounted  
034-370211D



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.2	0.27	0.33	0.4	0.5	0.57

## Sound absorption coefficient ( $\alpha_p$ )

