

# SASSO 100 round adjustable

trimless exposed concrete

048-2720E11W 048-2795210 002-90776



Project / Type

Notes

Count / Date



↑ IP20

↓ IP40

220-240V

360°

X-PERT

X-PERT

General

Ceiling , Recessed

tilt max 30°

rotation 360°

black , RAL9005 <sup>1</sup>

front IP40 , back IP20

2190 lm

LED

colour warm dimming

1800 K - 3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 89 , R<sub>(1-15)</sub>: 89

MR 0.56

MDER 0.51

Optical

wide flood

beam angle 51°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrical

DALI-2

28.0 W

PC2 220-240V

78 lm/W

1 DALI Addr.

Physical

trimless

length 230 mm

width 230 mm


height 162 mm

Cutout


recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



Installation instructions

Lighting calculator

