

# SASSO 100 round downlight

trim 2 lamps

048-2700E14W 048-279831G 002-90776



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Recessed	
matt silver	
Mounting set silver-grey	
front IP40 , back IP20	
4520 lm	

## LED

colour warm dimming	
1800 K - 3000 K	
CRI $\geq 90$	
L90 / 50000 h	
initial MacAdam $\leq 3$ SDCM	
R <sub>g</sub> : 100 , R <sub>f</sub> : 89 , R <sub>f(1-15)</sub> : 89	
MR 0.56	
MDER 0.51	

## Optical

wide flood	
beam angle 51°	
PstLM $\leq 1.0$ <sup>1</sup>	
SVM $\leq 0.4$ <sup>1</sup>	

## Electrical

DALI-2	
56 W	
total insets 48 W	
PC2 220-240V	
81 lm/W	
1 DALI Addr.	

## Physical


trim	
length 218 mm	
width 118 mm	
height 75 mm	

## Cutout


diameter 105 mm	
length 205 mm	
min. ceiling thickness 2 mm	
max. ceiling thickness 25 mm	
recessed depth 100 mm	

<sup>1</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

